

PED
2014/68/ CE
CAT. II



FDX HOT CUBE

SKID · TRAILER



FW2

Pump with 3 integral ceramic pistons and brass pump head

Pompa con 3 pistoni in ceramica e testata in ottone

ONLY TRAILER VERSIONS

Water valve tank with brass filter and float, anti-scale pump with 2.5 l capacity tank

SOLO SU VERSIONI TRAILER

Aspirazione acqua da tanica con filtro in ottone e galleggiante, dosatore anticalcare con pompa e serbatoio da 2,5 lt



WHEELS ONLY TRAILER VERSIONS

RUOTE SOLO SU VERSIONI TRAILER




ONLY SKID VERSIONS

Direct water pumping system with self-cleaning filter and ionic anti-scale device

SOLO SU VERSIONI SKID

Sistema di aspirazione acqua diretta con filtro autopulente e dispositivo anticalcare ionico

SKID VERSION



GENERAL FEATURES · CARATTERISTICHE GENERALI

- Professional hot water high pressure cleaner for uses without connection to electricity grid
- Honda GX 390 engine (gasoline models) or Yanmar L100V engines (Diesel models)
- Electrical starting-up
- No engine-oil safety device (oil-alert)
- Automatic decelerator to reduce RPM in by-pass mode
- Gearbox
- Fuel tank with level float and fill up filter
- Professional gradual pressure restoration unloader valve
- Double coil vertical stainless steel high efficiency boiler with stainless steel outer casing
- Electronic temperature setting system with constant water temperature
- PED 2014/68/CE cat. II certification
- Flow-switch operated burner
- Safety valve
- Boiler thermal protection
- Flame control kit
- Idropultrice professionale a caldo per utilizzo senza allacciamento alla rete elettrica
- Motore Honda GX 390 (modelli a benzina) o Yanmar L100V (modelli Diesel)
- Avviamento elettrico
- Dispositivo di Sicurezza mancanza olio motore
- Deceleratore automatico per la riduzione del numero di giri in fase di by-pass
- Riduttore di giri
- Serbatoio gasolio con galleggiante livello e filtro di riempimento
- Valvola regolazione professionale a ripristino graduale della pressione
- Caldia verticale in acciaio inox ad alto rendimento con serpentina a doppia spirale
- Sistema elettronico di regolazione della temperatura, con basso pendolamento del valore impostato
- Certificazione PED 2014/68/CE cat. II
- Brucciatoe azionato da Flussostato
- Valvola di sicurezza
- Protezione termica della caldaia
- Kit comando controllo fiamma
- Uso professionale intensivo

TECHNICAL FEATURES · CARATTERISTICHE TECNICHE

CODE CODICE	MODELS MODELLI	PUMP POMPA	MAX		WORK		l/h	°C	HP	kg/h	kg	(L x W x H) cm
			bar	MPa	bar	MPa						
TRAILER												
9058 1501	FDX Hot Cube 16/200 D Yanmar L 100 N	FW2	200	20	30÷190	3÷19	330÷960	85÷140	11	6,3	230	120 x 93 x 108
9058 1502	FDX Hot Cube 16/200 B Honda GX 390	FW2	200	20	30÷190	3÷19	330÷960	85÷140	13	6,3	200	120 x 93 x 108
9058 1503	FDX Hot Cube 21/160 D Yanmar L 100 N	FW2	160	16	30÷150	3÷15	560÷1260	85÷140	11	7,9	230	120 x 93 x 108
9058 1504	FDX Hot Cube 21/160 B Honda GX 390	FW2	160	16	30÷150	3÷15	560÷1260	85÷140	13	7,9	200	120 x 93 x 108
SKID												
9058 1513	FDX Hot Cube 16/200 D Yanmar L 100 N	FW2	200	20	30÷190	3÷19	330÷960	85÷140	11	6,3	230	120 x 93 x 108
9058 1512	FDX Hot Cube 16/200 B Honda GX 390	FW2	200	20	30>190	3÷19	330÷960	85÷140	13	6,3	200	120 x 93 x 108
on request	FDX Hot Cube 21/160 D Yanmar L 100 N	FW2	160	16	30÷150	3÷15	560÷1260	85÷140	11	7,9	230	120 x 93 x 108
on request	FDX Hot Cube 21/160 B Honda GX 390	FW2	160	16	30÷150	3÷15	560÷1260	85÷140	13	7,9	200	120 x 93 x 108

STANDARD EQUIPMENT · DOTAZIONE STANDARD

 <p>SKID TRAILER</p> <p>GH 401 gun with Swivel (n.2 o-ring) Pistola GH 401 con Swivel (n.2 o-ring)</p>	 <p>SKID TRAILER</p> <p>Bent double barrel lance, without nozzles Lancia a canna doppia angolata, senza ugelli</p>	 <p>SKID TRAILER</p> <p>Detergent nozzle for double barrel lance, 1/4" MEG connection Ugello detergente per lancia canna doppia, attacco 1/4" MEG</p>	 <p>SKID TRAILER</p> <p>Flame control kit Kit comando controllo fiamma</p>
 <p>SKID TRAILER</p> <p>Fan shape nozzle 25°, 1/4" MEG connection Ugello con getto a lama 25° attacco 1/4" MEG</p>	 <p>SKID TRAILER</p> <p>10 m rubber delivery hose kit Kit tubo gomma mandata 10 m</p>	 <p>SKID TRAILER</p> <p>RPM decelerator kit Kit deceleratore di giri motore</p>	