



# M 200

## CLASSIC · EXTRA

SELF-PRIMING PUMPS 



Ergonomic handle for easy maneuverability

*Maniglia ergonomica per una pratica movimentazione*



**ON CLASSIC VERSIONS**

Without hose reel at the top

**SU VERSIONI CLASSIC**

*Dotazione senza avvolgitubo nella parte superiore*



### MTP GXR · AXR

Motorpump with brass head and stainless steel pistons (GXR) or ceramic pistons (AXR) with valve and pressure gauge

*Motopompa con testata in ottone e pistoni in acciaio inox (GXR) o in ceramica (AXR) con valvola e manometro*




Removable detergent tank with externally visible level

*Serbatoio detergente estraibile con livello visibile esternamente*



Can be used vertically or horizontally

*Utilizzabile in verticale o in orizzontale*



GENERAL FEATURES · CARATTERISTICHE GENERALI

- Sturdy injection-moulded plastic casing
- Handy lance and gun storage
- Handle with supports for the power cable and delivery hose
- Easy maintenance by simply removing the front casing
- Big wheels (220 mm Ø) for easy movement up and down steps and over uneven ground
- Removable detergent tank with level visible from the outside
- Detergent adjustment with filter
- Regulated low-pressure detergent suction
- GXR motorpump with brass head and stainless steel pistons (monophase models); AXR motorpump with brass head and ceramic pistons (three-phase models)
- 2-pole motor (2800 rpm)
- Built-in professional unloader valve + gauge
- Total Stop system
- **Self-priming** pumps with EASY START device
- Rotary switch
- Motor thermal protection
- Robuste carenature in materiale plastico stampato ad iniezione
- Pratico alloggiamento della pistola e della lancia
- Manico con supporti di cavo alimentazione e tubo mandata
- Facilità di manutenzione con la semplice rimozione della arenatura frontale
- Ruote di grandi dimensioni (Ø 220 mm) per una facile movimentazione su gradini e terreni accidentati
- Serbatoio detergente estraibile con livello visibile esternamente
- Regolazione detergente con filtro
- Aspirazione detergente in bassa pressione con regolazione
- Motopompa GXR con testata in ottone e pistoni in acciaio inox; motopompa AXR con testata in ottone e pistoni in ceramica (modelli trifase)
- Motore a 2 poli (2800 giri/min)
- Valvola di regolazione professionale integrata + manometro
- Dispositivo Total Stop
- Pompa **autoadescante** con dispositivo EASY START
- Interruttore rotativo
- Protezione termica motore
- Uso semiprofessionale gravoso

TECHNICAL FEATURES · CARATTERISTICHE TECNICHE

CODE CODICE	MODELS MODELLI	PUMP POMPA															
			Ph	V	Hz	bar	MPa	bar	MPa	l/h	HP	kW	kW	lit	kg	(L x W x H) cm	
9057 1500 ●	M 200 10/150 M Classic	GXR	1	230	50	150	15	30÷135	3÷13,5	280÷600	3,0	2,2	2,9	3,5	37	54 x 44 x 68	
9057 1501 ●	M 200 10/150 M Extra	GXR	1	230	50	150	15	30÷135	3÷13,5	280÷600	3,0	2,2	2,9	3,5	47	54 x 44 x 99	
9057 1504 ●	M 200 12/130 M Classic	GXR	1	230	50	130	13	30÷120	3÷12	360÷720	3,0	2,2	2,9	3,5	37	54 x 44 x 68	
9057 1505 ●	M 200 12/130 M Extra	GXR	1	230	50	130	13	30÷120	3÷12	360÷720	3,0	2,2	2,9	3,5	47	54 x 44 x 99	
9057 1506 ●	M 200 12/200 T Classic	AXR	3	400	50	200	20	30÷190	3÷19	290÷720	5,0	3,7	4,3	3,5	40	54 x 44 x 68	
9057 1507 ●	M 200 12/200 T Extra	AXR	3	400	50	200	20	30÷190	3÷19	290÷720	5,0	3,7	4,3	3,5	50	54 x 44 x 99	

STANDARD EQUIPMENT · DOTAZIONE STANDARD

GC 201 gun with protection <i>Pistola GC 201 con protezione</i>	Bent lance, with adjustable nozzle <i>Kit lancia angolata, con ugello regolabile</i>	GC 251 gun with protection <i>Pistola GC 251 con protezione</i>	Bent lance with detergent head, with nozzle <i>Lancia angolata con testina detergente, con ugello</i>
<b>EXTRA</b>	<b>CLASSIC</b>	<b>EXTRA</b>	<b>CLASSIC   EXTRA</b>
Bent lance, with rotating nozzle <i>Lancia angolata, con ugello rotante</i>	10 m rubber delivery hose kit <i>Kit tubo gomma mandata 10 m</i>	Hose Reel with 15 m rubber delivery hose <i>Avvolgitubo con tubo mandata 15 m</i>	Plastic inlet water filter <i>Filtro ingresso acqua in plastica</i>