



SELF-PRIMING PUMPS



ETM

X · PRO



Pressure regulating knob with anti-tampering device

Manopola regolazione pressione con dispositivo anti-manomissione



LW-K 250

PRO VERSIONS

Pump with 3 integral ceramic pistons. Oil sight glass. Brass pump heads

VERSIONI PRO

Pompa con 3 pistoni in ceramica integrale. Visore livello olio. Testate in ottone



GXR

X VERSIONS

Comet electrical pump with three axial pistons arranged vertically with pump at the bottom and an all-metal construction without any plastic used for the structural components

VERSIONI X

Elettropompa Comet a tre pistoni assiali disposta in verticale con pompa in basso e costruzione interamente in metallo, senza materiale plastico nei componenti strutturali



FOR MORE INFO:
MAGGIORI INFORMAZIONI:



GENERAL FEATURES · CARATTERISTICHE GENERALI

- Easy to transport thanks to a practical top grip and anti-vibration supports
- Induction 2-pole motor (2800 rpm) on ETM 150 X model
- 4-pole motor (1400 rpm) on ETM 150 PRO model
- Built-in professional unloader valve with ejector
- EASY START device
- Total Stop system
- Rotary switch
- Motor thermal protection
- Semplicità di trasporto mediante confortevole impugnatura superiore ed appoggio su supporti antivibranti
- Motore a 2 poli a induzione (2800 giri/min) per modello ETM 150 X
- Motore a 4 poli (1400 giri/min) per modello ETM 150 PRO
- Valvola di regolazione professionale integrata con eiettore
- Dispositivo EASY START
- Dispositivo Total Stop
- Interruttore rotativo
- Protezione termica del motore
- Uso semiprofessionale gravoso (uso professionale per ETM 150 PRO)

TECHNICAL FEATURES · CARATTERISTICHE TECNICHE

CODE CODICE	MODELS MODELLI	PUMP POMPA								
			Ph V Hz	bar MPa	bar MPa	l/h	HP kW	kW	kg	(L x W x H) cm
9055 0016	ETM 150 X	GXR	1 230 50	150 15	30 ÷ 135 3 ÷ 13,5	280 ÷ 600	3 ,0 2,2	2,9	25	26 x 47 x 37
9055 0011	ETM 150 PRO	LW-K 250	1 230 50	150 15	30 ÷ 135 3 ÷ 13,5	280 ÷ 600	3 ,0 2,2	2,9	35	26 x 47 x 37

STANDARD EQUIPMENT · DOTAZIONE STANDARD

X  GC 201 gun with protection Pistola GC 201 con protezione	PRO  GC 251 gun with protection Pistola GC 251 con protezione	X  Lance with adjustable jet, with nozzle Lancia getto regolabile con ugello
PRO  Bent lance with detergent head, without nozzle Lancia angolata con testina detergente, senza ugello	PRO  15° spray nozzle, 1/4" MEG connection Ugello con getto a lama 15° attacco 1/4" MEG	X PRO  R1 1/4" 10 m rubber delivery hose kit Kit tubo mandata in gomma 10 m R1 1/4"